

# 7000X Series

WITH CAPACITIVE RECOGNITION

CERTIFIED BY TÜV SÜD

OPTIONAL WIFI MODULE

OPTIONAL PC MODULE  
 6 USB 3.0 Ports  
 1 LAN (RJ45)  
 1 VGA Output  
 1 Earphone Output  
 1 Microphone Input  
 1 Display Port Output  
 1 HDMI Output

RIGHT SIDE  
 1 USB 3.0 Port  
 3 USB 2.0 Port  
 2 Touch Inputs  
 1 VGA Input  
 1 Audio Input  
 2 HDMI Input  
 1 HDMI Output

BOTTOM  
 1 USB 2.0 Port  
 1 AV Input  
 1 Audio Output  
 1 SPDIF  
 1 RS232 Port  
 1 RJ45 Port

Optional PC Module

Optional WiFi Module

### Panel Operating System

System Version. . . . . Android 7.0  
 CPU . . . . . A73x2  
 GPU . . . . . Mali 450x5  
 RAM . . . . . 2GB  
 ROM . . . . . 16GB

### Panel Interactivity

Sensing Type . . . . . Capacitive recognition  
 Compatibility . . . . . Windows, MacOSX, Android, Linux, Chrome  
 Touch Point . . . . . 10 points writing  
 20 points touch  
 Touch Tool . . . . . Finger  
 Capacitive stylus  
 Response Time. . . . . <30 ms  
 Accuracy . . . . . 1 mm  
 Touch Recognition . . . . . Palm Rejection  
 Simultaneous multiple colors  
 Simultaneous multiple pens  
 Pressure sensitivity  
 Surface Hardness . . . . . 7 mohs toughened glass  
 Output Coordinate . . . . . 32767 x 32767

### Panel Ambient

Operation Temperature . . . . . 32°F – 104°F  
 Operation Humidity . . . . . 10% – 90%  
 Storage Temperature . . . . . -4°F – 140°F  
 Storage Humidity . . . . . 10% – 90%  
 Altitude . . . . . Below 16404.2'

### Included Accessories

2 pens, remote control, 2 AAA batteries, power cord, HDMI cable, USB touch cable



	7055X ULTRA HD	7065X ULTRA HD	
<b>Display</b>			
Size	55"	65"	
Panel Type	IPS	•	
Aspect Ratio	16:9	•	
Resolution	3840 x 2160 Ultra HD	•	
Display Area	47.62" x 26.79"	56.24" x 31.63"	
Pixel Pitch	.315mm x .315mm	.372mm x .372mm	
Back Light Unit	Direct type LED	•	
Response Time	6 ms	9 ms	
Refreshing Frequency	60Hz	•	
Display Color	1.07B (10bit)	•	
Brightness	350 cd/m <sup>2</sup>	•	
Contrast Ratio	1200:1	•	
Viewing Angle	178°	•	
Life Time	30,000 hours	•	
<b>Audio</b>			
Speaker Type	Built-in speaker	•	
Output Power	10W + 15W x 2	•	
<b>Connectors</b>			
USB 2.0	4	4	
USB 3.0	•	•	
Touch Input	2	2	
HDMI Input 2.0	2	2	
VGA Input	•	•	
Audio Input	•	•	
AV Input	•	•	
HDMI Output 2.0	•	•	
Audio Output	•	•	
RS232 Port	•	•	
RJ45 Port	•	•	
SPDIF	•	•	
<b>Power</b>			
Power Requirements	100-240V~ 50/60Hz	•	
Standby Power	≤0.5W	•	
Overall Power (nominal)	250W	300W	
<b>Physical Specifications</b>			
Key Location	Right side	•	
Dimension	L x W x D	49.96" x 29.41" x 3.43"	58.78" x 34.33" x 3.46"
Package Dimension	L x W x H	56.22" x 8.66" x 33.27"	66.8" x 8.66" x 40.9"
Net Weight		63.93 lbs	98.44 lbs
Gross Weight		89.51 lbs	131.09 lbs
Machine + Wall Mount Thickness (CTI-MOUNT-FIXW)		5.24"	5.28"
Wall-hanging Screw Spec	M8 x 25 mm	•	•
VESA		400 x 200 mm	600 x 400 mm