

UHD Signage 98/86/75" UH5F-H

LG UHD Large Screen Signage



Large Screen Size



Clear View with Non-glare Coating



Superb Picture Quality







SUPERB PICTURE QUALITY



Clear View with Non-glare Coating

Viewers can be annoyed by unnecessary reflections when watching a screen under brightly lit conditions. The UH5F-H series has resolved such inconveniences by increasing the level of haze, which enhances visibility and text readability.



ULTRA HD Resolution

With the resolution that is 4 times higher than FHD, it makes the color and details of the contents more vivid and realistic. In addition, the wide viewing angle applied with an IPS panel, provides vivid, clear contents viewable even at wide angles.

webOS SMART SIGNAGE PLATFORM



High-Performance with webOS

Built-in Quad Core System on Chip can execute several tasks at once while providing smooth content playback without the need for a media player. Also, LG webOS smart signage platform enhances user convenience with intuitive iser interface and simple app development tools.



Various Sensor Applications

LG webOS smart signage platform supports connections with external sensors such as GPIO, NFC/RFID, temperature sensors, etc, via USB plug-in. There is no need to purchase additional software or media players for creating value-added solutions.

MEETING ROOM SOLUTION COMPATIBILITY



Compatible with AV Control System

The UH5F-H series has been certified Crestron Connected® for high compatibility with professional AV controls to achieve seamless integration and network-based control*, boosting business management efficiency.



Compatible with Video Conference System

The UH5F-H series is compatible with Cisco systems using an HDMI cable connection. This offers powerful and integrated control for a smarter video conference, virtually eliminating wasted time setting up the picture quality or changing inputs for incoming calls.

EASY MANAGEMENT



Real-time Monitoring & Control

Through the Control Manager, the embedded web monitoring solution, you can control and monitor the status of multiple UH5F-H series displays in different locations in real-time. It is available on internet connected devices, allowing you to flexibly and rapidly respond to emergency situations anywhere.




LG ConnectedCare

The maintenance gets easier and faster with an optional service LG ConnectedCare*, a cloud service solution provided by LG service. It remotely manages status of displays in client workplaces for fault diagnosis and remote-control services, ensuring the stable operation of a client's business.

* The availability of "LG ConnectedCare" service can differ by region, so please contact the LG sales representative in your region for further details.

USER CONVENIENCE



Multiscreen Feature with PBP / PIP

Picture-by=Picture (PBP) features multiple screens in a single display with up to 4 input sources while PIP (Picture-In-Picture) supports playing both a main screen and a subscreen at the same time with various layouts. This gives great flexibility to allocate space for each content source.





Wireless Access Point

The UH5F-H series operates as a virtual router which can be an wireless access point for mobile devices.


DIMENSIONS


98"







86"





75"







CONNECTIVITY

98"

Bottom




Side




86" / 75"

Bottom



Side



- 1 AUDIO IN
- 5 HDMI IN 2
- 9 HDMI IN 3
- 13 RS-232C IN

- 2 AUDIO OUT
- 6 IR / LIGHT SENSOR
- 10 DVI D IN
- 14 RS-232C OUT

3 LAN

- 7 DP IN
- 11 USB IN 1

- 4 HDMI IN 1
- 8 DP OUT
- 12 USB IN 2

^{*} Dimensions & Jack Panels may differ from the above image, so please contact LG sales team to verify before ordering.

SPECIFICATIONS

DANEL		98UH5F-H	86UH5F-H	75UH5F-H
PANEL	Screen Size	98"	86"	75"
	Panel Technology	IPS Direct	IPS Edge	IPS Edge
	Back Light Type Aspect Ratio	<u>Direct</u> 16:9	Edge 16:9	Edge 16:9
	Native Resolution	3840 x 2160 (UHD)	3840 x 2160 (UHD)	3840 x 2160 (UHD)
	Refresh Rate	120 Hz	120 Hz	120 Hz
	Brightness (Typ)	500 nits	500 nits	500 nits
	Contrast Ratio Dynamic CR	1,200:1 1,000,000:1	1,100:1 1,000,000:1	1,100:1 1,000,000:1
	Color gamut	NTSC 72%	NTSC 72%	NTSC 72%
	Viewing Angle(H x V)	178° X 178°	178° X 178°	178° X 178°
	Color Depth	10 bit, 1.07 Billion colors	10 bit, 1.07 Billion colors	10 bit, 1.07 Billion colors
	Response Time (G to G)	8 ms	8 ms	6 ms
	Surface Treatment (Haze) Lifetime	28% 50,000 Hrs	28% 50,000 Hrs	28% 50,000 Hrs
	Operation Hours (Hours/Day)	24/7	24/7	24/7
	Portrait / Landscape	Yes / Yes	Yes / Yes	Yes / Yes
OUND	Speaker	Yes	Yes	Yes
	HDMIIN	l .	Yes (3) HDMI1/HDMI2: HDCP 2.2/1.4, HDMI3: HDCP 1.4	
CONNECTIVITY	DP IN	Yes (1), HDCP2.2/1.3	Yes (1), HDCP2.2/1.3	Yes (1), HDCP2.2/1.3
	DVI-D IN	Yes (1), HDCP1.4	Yes (1), HDCP1.4	Yes (1), HDCP1.4
	Audio In	Yes Yes	Yes Yes	Yes
	RS232C IN RJ45 (LAN) IN	Yes (1), 4pin 3.5mm Jack	Yes (1), 4pin 3.5mm Jack	Yes (1), 4pin 3.5mm Jack
	IR IN	Yes Yes	Yes Yes	Yes Yes
	USBIN	USB2.0 Type A(2)	USB2.0 Type A(2)	USB2.0 Type A(2)
	DP Out	Yes (1), Input: HDMI1/2/3/DVI/DP	Yes (1), Input: HDMI1/2/3/DVI/DP	Yes (1), Input: HDMI1/2/3/DVI/DP
	Audio Out	Yes	Yes	Yes
	RS232C OUT Bezel Color	Yes (1), 4pin 3.5mm Jack Black	Yes (1), 4pin 3.5mm Jack Black	Yes (1), 4pin 3.5mm Jack Black
IECHANICAL	Bezel Width	Even bezel: 14.9mm	Even bezel: 14.3mm	Even bezel: 14.9mm
	Weight(Head)	178.8 lbs / 81.1 kg	108.0 lbs / 49.0 kg	91.5 lbs / 41.5 kg
	Packed Weight	262.4 lbs / 119 kg	159.8 lbs / 72.5 kg	112.9 lbs / 51.2 kg
	Monitor Dimension (W x H x D)	86.3 x 49.1 x 3.3 in / 2191.8 x 1246.8 x 83.8 mm (without Handle and LG Logo)	75.8 x 43.2 x 2.4 in / 1926.2 x 1097.2 x 60.6 mm (without Handle and LG Logo)	66.2 x 37.8 x 2.3 in / 1682.4 x 960.3 x 57.9 mm (without Handle and LG Logo)
		` ,	` '	
	Carton Dimensions (W x H x D) (Box outer size)	93.0 x 54.6 x 16.5 in / 2362 x 1386 x 420 mm	81.6 x 49.2 x 11.2 in / 2073 x 1250 x 285 mm	71.5 x 44.2 x 9.0 in / 1816 x 1123 x 228 mm
	Handle	Yes	Yes	Yes
	VESATM Standard Mount	800 x 400	600 x 400	600 × 400
	Interface Tilt (Face Down)	No No	No	No
	Operation Temperature	32°F to 104°F / 0°C to 40°C	32°F to 104°F / 0°C to 40°C	32°F to 104°F / 0°C to 40°C
	Operation Humidity	10 % to 80 %	10 % to 80 %	10 % to 80 %
	OPS type compatible	No	Yes	Yes
	OPS Power built in	No 0.60	Yes	Yes
Y FEATURES	Internal Memory Built-in Wi-Fi	8 GB Yes	8 GB Yes	8 GB Yes
	Temperature Sensor	Yes	Yes	Yes
	Auto Brightness sensor	Yes	Yes	Yes
	Local Key Operation	Yes	Yes	Yes
	webOS ver. Local Contents Scheduling	webOS 4.0	webOS 4.0	webOS 4.0
	Group Manager	Yes Yes	Yes Yes	Yes Yes
	USB Plug & Play	Yes	Yes	Yes
	Fail over	Yes	Yes	Yes
	Booting Logo Image	Yes	Yes	Yes
	No Signal Image RS-232C Sync	Yes Yes	Yes Yes	Yes
	Local Network Sync	Yes	Yes	Yes Yes
	PIP	Yes	Yes	Yes
	PBP	Yes (4)	Yes (4)	Yes (4)
	Screen Share	Yes	Yes	Yes
	Video Tag	Yes (4)	Yes (4)	Yes (4)
	Play via URL Screen Rotation	Yes Yes	Yes Yes	Yes Yes
	External Input Rotation	Yes	Yes	Yes
	Gapless Playback	Yes	Yes	Yes
	Tile Mode Setting	Yes (Max. 15x15)	Yes (Max. 15x15)	Yes (Max. 15x15)
	Setting Data Cloning SNMP	Yes Yes	Yes Yes	Yes Yes
	ISM Method	Yes	Yes	Yes
	Auto Set ID	Yes	Yes	Yes
	Status Mailing	Yes	Yes	Yes
	Control Manager	Yes	Yes	Yes
	Crestron Inside	Yes	Yes	Yes Yes
			YAS	
	Smart Energy Saving PM mode	Yes Yes	Yes Yes	Yes
	PM mode Wake on LAN	Yes Yes	Yes Yes	Yes Yes
	PM mode Wake on LAN Beacon	Yes Yes Yes	Yes Yes Yes	Yes Yes Yes
	PM mode Wake on LAN Beacon HDMI-CEC	Yes Yes Yes Yes	Yes Yes Yes Yes	Yes Yes Yes Yes
	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting	Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes
	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proddiom	Yes	Yes	Yes
OWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz	Yes Yes Yes Yes Yes Yes Yes Yes Yes Your Ses Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes Of Dock Of
DWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type	Yes	Yes	Yes
OWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power	Yes	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Bullt-in Power 180W
OWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type	Yes	Yes	Yes
OWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving	Yes	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 180W 260W 614.25 BTU/Hr (Typ), 887.25 BTU/Hr (Max)"
OWER	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Protdiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 420W 560W 1433.25 BTU/Hr (Typ), 1911 BTU/Hr (Max) 294 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 215W 280W 733.69 BTU/Hr (Typ.) 955.5 BTU/Hr (Max) 150.5 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 180W 260W 614.25 BTU/Hr (Typ), 887.25 BTU/Hr (Max)" 126 W 0.5 W
	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 420W 560W 1433.25 BTU/Hr (Typ), 1911 BTU/Hr (Max) 294 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 215W 280W 733.69 BTU/Hr (Typ.) 955.5 BTU/Hr (Max) 0.5 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 180W 260W 260W 614.25 BTU/Hr (Typ.), 88725 BTU/Hr (Max)" 126 W 0.5 W
S SOFTWARE	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC ProIdiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign CMS	Yes	Yes	Yes
S SOFTWARE	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 420W 560W 1433.25 BTU/Hr (Typ), 1911 BTU/Hr (Max) 294 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Ses Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 215W 280W 733.69 BTU/Hr (Typ.) 955.5 BTU/Hr (Max) 0.5 W 0.5 W	Yes Yes Yes Yes Yes Yes Yes Yes Yes Solution Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 180W 260W 614.25 BTU/Hr (Typ), 887.25 BTU/Hr (Max)" 126 W 0.5 W 0.5 W
s SOFTWARE	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC ProIdiom Power Supply Power Type Typ, Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign CMS SuperSign Control / Control+ SuperSign WeB SuperSign WB SuperSign MeB	Yes	Yes	Yes
s SOFTWARE	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign Media Editor Signage 365 Care	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Bult-in Power 420W 560W 560W 1433.25 BTU/Hr (Typ), 1911 BTU/Hr (Max) 294 W 0.5 W 0.5 W Yes Yes Yes Yes Yes Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes Solfon Hz Built-in Power 215W 280W 733.69 BTU/Hr (TJp.) 955.5 BTU/Hr (Max) 0.5 W 0.5 W Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Bult-in Power 180W 260W 260W 0.5 W 0.5 W 0.5 W Yes Yes Yes Yes
S SOFTWARE SERVICES* VARRANTY	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC ProIdiom Power Supply Power Type Typ. Power Max. Power Max. Power BTU (British Thernal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign WB SuperSign Media Editor Signage 355 Care Warranty	Yes	Yes	Yes
S SOFTWARE SERVICES*	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC ProIdiom Power Supply Power Type Typ. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off Super-Sign CMS Super-Sign CMS Super-Sign WB Super-Sign Media Editor Signage-365 Care Warranty FCC (Regulatory)	Yes	Yes	Yes
G SOFTWARE SERVICES*	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign Media Editor Signage 365 Care Warranty FCC (Regulatory) CE (Regulatory)	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 215W 280W 733.69 BTU/Hr (Typ.) 955.5 BTU/Hr (Max) 150.5 W 0.5 W Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 180W 260W 260W 614.25 BTU/Hr (Typ.), 887 25 BTU/Hr (Max)" 126 W 0.5 W 0.5 W Yes
G SOFTWARE SERVICES*	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power Max. Power Max. Power Max. Power Max. Power STU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign WB SuperSign WB SuperSign WB SuperSign WB Control / Control+ SuperSign WB Control / Control+ Control / Control Cont	Yes	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 180W 260W 614.25 BTU/Hr (Typ), 887.25 BTU/Hr (Max)" 126 W 0.5 W 0.5 W Yes
G SOFTWARE : SERVICES*	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power Max. Power BTU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign Media Editor Signage 365 Care Warranty FCC (Regulatory) CE (Regulatory)	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-in Power 215W 280W 733.69 BTU/Hr (Typ.) 955.5 BTU/Hr (Max) 150.5 W 0.5 W Yes	Yes
G SOFTWARE SERVICES* WARRANTY OTHER"	PM mode Wake on LAN Beacon HDMI-CEC SI Server Setting webRTC Proldiom Power Supply Power Type Typ. Power Max. Power Max. Power Max. Power Max. Power Max. Power STU (British Thermal Unit) Smart Enegy Saving DPM Power off SuperSign Control / Control+ SuperSign WB SuperSign WB SuperSign WB SuperSign WB Control / Control+ SuperSign WB Control / Control+ Control / Control Cont	Yes	Yes	Yes Yes Yes Yes Yes Yes Yes Yes Yes 100-240 Vac, 50/60 Hz Built-In Power 180W 260W 614.25 BTU/Hr (Typ), 887.25 BTU/Hr (Max)" 126 W 0.5 W 0.5 W Yes

 $^{* \, {\}sf SuperSign} \, {\sf CMS}, \, {\sf Control+}, \, {\sf White} \, {\sf Balance} \, {\sf and} \, {\sf Signage365} \, {\sf Care} \, {\sf are} \, {\sf optional} \, {\sf pay-for} \, {\sf software/services}.$

