



Features

REDUCED TCO (Total Cost of Ownership)

The 84WS70MS-B and 84WS70BS-B display are Energy Star® 5.1 compliant consuming approximately 40% less energy than noncompliant models. In standby mode, it uses less than one watt of power and meets the environmental regulations while excluding the use of harmful materials (RoHS) and reducing CO2 emissions.

BEZEL WIDTH

This aesthetically superior display has the bezel width of 27.9mm that offers an elegant but modern look that will work well with any decor.

Specifications

Native Display Resolution 3840 x 2160 (Ultra HD) Brightness 500 cd/m² (84WS70MS-B)

250 L/ 2 (0.4)MC70DC D)

350 cd/m² (84WS70BS-B)

Contrast Ratio 1,400:1 (Typ.), 500,000:1 (DCR)

178°/ 178° Ultra Wide Viewing Angle

Can be installed in Portrait or Landscape mode

RGB input/output (1) DVI-D input/output (1)

HDMI input (2)

DisplayPort input (1)

Convenient External Speaker-Out

Smart Energy Saving Bezel Width 27.9mm

Temperature Sensor

USB Playback

3-Year Limited Warranty Parts/Labor/Backlight







NO BLACKENING DEFECT

Display has a built-in temperature control that adjusts to light and heat eliminating dark or blackened areas.



If the outdoor temperature is 86°F the surface temperature of display is 185°F

TRUE WIDE VIEWING

Color shifts and distortion are eliminated from any viewing angle.



Color change average @ 60° Gamma change average @ 60°

PANEL STABILITY

Minimized image distortion and shows no tailing when external pressure is applied.



IPS Competition


84" Edge LED Large Screen

The sheer size of the screen, equal to four 42-inch class displays, gives you a breathtaking viewing experience. The picture is so big and immersive, it's as if you're in the scene and part of the action.



Attachable External Media Players (sold separately)

Slim design LG media players can be installed conveniently in the back without taking up additional space.



Slot type Media Player

Super High Resolution 3,840 x 2,160 (Ultra HD)

Boasting a pixel resolution 4X higher than Full HD (1080p), its detail is so vivid and crisp, even when viewed from a close distance.



When using the MP700 follow these tips to achieve the best playback quality

Create content based on the same resolution as the digital signage monitor

Video content should be encoded at above an optimum level of bit rate

- Playback content larger than its original size
- Increasing bit rate will improve the quality of content, but requires high performing CPU
- •Dynamic content such as sports may require a higher bit rate

Recommended content creation when using a CPU i7 $2.x\ GHz$


Recommendation	Ultra HD Signage	FHD Signage	HD Signage
Resolution	3,840 x 2,160	1,920 x 1,080	1,366 x 768
Bit Rate	80~120Mbps (full motion video) over 40Mbps (slideshow video)	over 20 Mbps (full motion video) above 10Mbps (slideshow video)	10 Mbps (full motion video) over 5Mbps (slideshow video)
Appropriate FPS/Hz	30 FPS	30 FPS	30 FPS
Codec	H.264>MPEG4>MPEG2 (bigger file size)	H.264>MPEG4>MPEG2 (bigger file size)	H.264>MPEG4>MPEG2 (bigger file size)
Codec Pack	K-Lite CodecPack	K-Lite CodecPack	K-Lite CodecPack




LG is committed to improving product development, manufacturing and usage to meet the demand for products with environmentally friendlier features. Our Display has technologies to reduce power consumption and in return increase cost savings per room.

EcoSmart

- Intelligent Sensor Continually monitors room light conditions to automatically
 optimize the picture quality for a more enjoyable viewing experience, which
 can help save energy.
- Dynamic Power Savings Using built-in algorithms, Display will automatically reduce the power consumption based on incoming video, while maximizing picture performance.
- Static Power Savings Picture brightness level can be set at the preferred power consumption level to reduce power and increase energy savings.
- CEC Compliant Meets the Appliance Efficiency Regulations of the California Energy Commission.
- RoHS Compliant Meets directive on restriction of hazardous substances.



Rear Jack Panel



LED Widescreen Ultra HD Display





▶84WS70BS-B

84" class (84.04" measured diagonally)

PANEL	Model	84WS70MS-B	84WS70BS-B	
	Screen Size	84" (84.04" measur	ed diagonally)	
	Panel Technology	IPS		
	Aspect Ratio	16:9		
	Native Resolution	3840 x 2160 (UD)		
	Pixels(H x V x 3)	24,883,200		
	Brightness	500 cd/m ²	350 cd/m ²	
	Contrast Ratio	1,400:1		
	Dynamic CR	500,000 : 1		
	Color Gamut	72%		
	Tni	110°C (=230°F)		
	Viewing Angle	178°/178°		
	Color Depth	1.06 Billion		
	Response Time	12ms (G to G)		
	Surface Treatment	Anti-glare(Haze <10%)		
	Orientation	Portrait and Landscape	Landscape only	
VIDEO (PC)	Max Input Resolution	3840 x 2160@30Hz (HDMI, Display Port) 1920 x 1080@60Hz (RGB, DVI-D)		
	Rec. Resolution	3840 x 2160@30Hz(HDMI, Display Port)		
	H-Scanning Freq	30 ~ 83kHz (RGB, HDMI/DVI-D/DP)		
	V-Scanning Freq	56Hz ~ 75Hz (RGB), 56Hz~60Hz (HDMI/DVI-D/DP)		
	Pixel Frequency	300MHz(HDMI, Display Port) 148.5MHz(RGB, DVI-D)		
	Sync Compatability	Separate, Composite, Digital		
	Video Input	RGB, HDMI, DVI-D, Display Port, Composite		
	Picture mode	Intelligent Sensor/Vivid / Standard / Cinema / Game/ Expert1/Expert2		
	Color temperature	Warm, Medium , Cool		
CONNECTIVITY INPUT (Rear)	Digital	HDMI(2), DVI-D(1), Display Port(1) with HDCP for all input		
	Analog	RGB(1), Composite(1)		
	Audio	·		
	External Control RS232C(1), RJ45(1), IR(1)		45(1), IR(1)	
	USB USB(2)			
	HDTV Formats	Component: 720p, 1080i , 1080p HDMl: 720p, 1080i, 1080p, 2160p		
OUTPUT (Rear)	Digital	DVI-D(1)		
	Analog	RGB(1)		
	Audio	Yes(1)		
	External Control	RS232C(1), IR(1)		
AUDIO	Balance	Yes		
	Audio Power	20W (10W x 2)		
	Speaker on/off	Yes		
	Clear Voice II	Yes		
	Sound Mode	Standard / Music / Cinema / Spor	t / Game /Vivid/ User Setting	

PHYSICAL SPECIFICATIONS	Model	84WS70MS-B	84WS70BS-B			
	Color	Black				
	Bezel Width	27.9mm				
	Monitor Dimensions	75.7" x 4.0" x 43.7" (W x H x D) (head only)				
	Monitor Weight 160.7 lbs. (head only)					
	Carton Dimensions	80.0" x 12.4" x 47.8 (W x H x D)				
	Packed Weight	192.2 lbs.				
		Yes				
	Handle	tes				
	VESA™ Standard Mount Interface	600mm x 400mm				
SPECIAL	Temperature Sensor					
FEATURES	Auto Brightness Sensor					
	Source Selection: AV, Component, RGB, Display Port, DVI-D, HDMI					
	Brightness/Contrast/Backlight					
	Position/Size					
	Auto Config/Phase English, French, German, Spanish, Italian, Korean , Chinese(Simplified),					
	Language (OSD)	Chinese(Original), Portugues(Brazil),	Italian, Korean , Chinese(Simplified), Swedish, Finnish, Norwegian, Danish, (Europe), Dutch, Czech, Greek			
	Language (USB Playback)	English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Japanese, Russian, Portugues(Europe), Dutch, Czech, Greek				
	Language (Manual)	English, French, Italian, German, Spanish, Portugues, Hungarian, Greek, Russian, Dutch, Kazakh, Ukrainian, Polish, Arabic, Indonesian, Korean, Japanese, Turkish, Czech, Taiwanese, Slovak				
	Language (ESG)	·	h, Portugues, Greek, Polish, Czech, Slovak			
	ISM Method		ish, Orbiter, Inversion			
	Advanced		ear White, Skin Color, Noise Reduction, on, Gamma, Black Level			
	Time	-	er on Delay, Auto Off, Automatic Standby			
	Information Model/Type, Software Version, Serial MAC Address, Homes					
	Input Label		C/DTV)			
	Auto Power/Source Yes		/es			
	Key Lock					
	DPM Select					
	Energy Saving Yes (Minimum, Medium, Maxium)					
	Smart Energy Saving					
	Power Indication On/Off					
	File Play with USB					
ENVIRONMENT CONDITIONS	Operation Temp.		~ 40°C			
	Operation Humidity		~ 80%			
POWER	Power Supply	100 -240V	~, 50/60Hz			
	Power Consumption	Normal (Ty	pical) 350W			
		Smart Energy S	Saving on 200W			
		DPMS Off 1.5W(RGB)				
		Power Off 0.5W				
STANDARD	Safety	UL/cUL/CE	3 scheme / TUV			
CERTIFICATION	EMC	FCC Class "A", VCCI, C-tick, CE, KCC				
MEDIA PLAYER COMPATIBILITY	Yes (MP500, MP700)					
WARRANTY	3-Year Limited Warranty (Parts/Labor/Backlight)					
UPC	7 19192 19191 4 7 19192 19192 1					
OPTIONAL ACCESSORIES	D-Sub Cable, Power Cord, Remote Controller(include battery 2ea), CD(Manual/Elite-C), Eye Bolt(2EA) Media Player: MP700/MP500					
	Media Flayer: MP/U	U/ MF300				







Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com











All screen images are simulated. Dimensions and weights are approximate. Design, specifications, and features subject to change without notice.

@ Copyright 2013 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. In Plane Switching is a trademark of LG Philips LCD Ltd. VESA is a trademark of Video Electronics Standards Association. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

All other product and brand names are trademarks or registered trademarks of their respective companies.

